VORTEX

sales@maxliner.co.uk | www.maxliner.co.uk



E-Mix XT

Electric Variable Ratio Sprayer

BREAKTHROUGH PERFORMANCE
- Variable Ratio from 1:1 to 6:1
- Flow rates up to 1.5 gpm
- 5,000 psi Max Pressure
- Tip support to .039

HIGH TORQUE MOTORS
- Low RPM, high torque design offers long life
- Silent operation for comfort and extending spray times in restricted areas

DUAL PUMPS
- Chromex Rod and Chrome cylinder for exceptional life and durability
- Balanced double-displacement design for ratio accuracy
- Quick and easy pump removal - perfect for on-the-job maintenance

DUALFLO™ ON-DEMAND FLUID HEATER
- Offers independent heat for A & B components
- 4,000 watt power provides up to 60°F delta T heat rise for easier spraying
- Adjusts right from the touch screen

EASY-TO-MANEUVER DESIGN
- Integrated lift points and flat proof tires



THE EASIEST-TO-OPERATE VARIABLE RATIO SPRAYER IN THE INDUSTRY

Economical and easy to operate, the E-MIX XT has been developed to work with all Quadex branded epoxy systems. Designed to handle spray ratios from 1:1 up to 6:1, it's an ideal sprayer for practically every job.

The 1:1 to 6:1 Variable ratio feature allows it to be used with:
- Structure Guard®
- Structure Guard®-Water
- Structure Guard®-RS
- Structure Guard®-QS
- Chimney Guard™
- Flex Guard®

KEY PERFORMANCE FEATURES
- Electric powered, no air compressor needed less hassle and expense — save $1000's per week!
- Easy touchscreen operation set ratio, pressure, heater temperatures and spray!
- Quiet operation allows extended spray times in noise-sensitive areas
- Offers substantial solvent and coating savings compared to "hot-potting"

Distributed By MAXLINER®

sales@maxliner.co.uk | www.maxliner.co.uk



ELECTRIC POWER!

TOUCH-SCREEN INTERFACE
- Spray parameters are controlled from one screen
- Eliminates the steep learning curve — no expert needed
- Perfectly syncs the motors and pumps to deliver the perfect ratio

FEATURING RATIOGUARD PROTECTION
- Real-time ratio monitoring maintains accuracy
- Integrated alarm system prevents errors and eliminates rework

INTEGRATED RATIO CHECK
- Proves on-ratio accuracy for each mix
- Ideal for inspections and quality control checks
- Single-handle design for easy, efficient operation

QUICK FLUSH SOLVENT PUMP
- Allows quick flushing of mix hose and gun during stoppage to protect your equipment
- Features 5 gallon inlet suction set for solvent bucket

Ready-to-Spray Solutions for Every Job

Choose from Standard Series for work where a remote manifold is not required, or the Pro Series for longer hose runs with a remote manifold.



E-MIX XT STANDARD INCLUDES
- E-Mix XT (240v 40a Single Phase)
- Dual 7 Gallon Hoppers
- FastClean Solvent Flush Pump
- DualFlo Heater
- Ratio Check Kit
- 25’ x ⅜” Mix Integration Hose
- 10’ x ¼” Whip Hose
- XTR 5+ Gun, XHD 519 Switch Tip



E-MIX XT PRO INCLUDES

All the Standard Features, PLUS:
- Light Tower
- Hose Rack
- Remote Manifold Carriage
- 200’ x ½” (4 x 50’) “A” & “B” Material Hose
- 100’ x ⅜” (2 x 50’) “B” Material Hose (ratios over 3:1)

E-MIX XT 240V
- E-Mix XT Standard Series: Part #2004087
- E-Mix XT Pro Series: Part #2005565