

Quadex OneGun®

Battery Operated, Dual Component Dispenser

Cartridged Repair Materials

THIS EXTREMELY POWERFUL AND ULTRA PORTABLE BATTERY OPERATED CARTRIDGE GUN IS THE PERFECT SOLUTION FOR APPLYING THE QUADEX® LINE OF DUAL COMPONENT REPAIR MATERIALS.



Quadex OneGun® is systematically designed to deploy the Quadex line of cartridged repair materials, whether in “1 to 1” or “2 to 1” ratios.

OneGun’s 20 Volt Lithium-Ion Battery will deliver up to three hours of continuous power in the most extreme conditions.

Benefits of using OneGun with Quadex patching and sealing products:

- **One delivery method, multiple repair materials**
- **Battery operation eliminates cords and hoses from the work area**
- **Resealable cartridges eliminate material waste**
- **Durable design to exist in the toughest of environments**

Distributed By

MAXLINER®

sales@maxliner.co.uk | www.maxliner.co.uk

Use these proven Quadex® products to ensure superior results!

Structure Guard® -FM

Micro-Fiber Reinforced Mastic

Structure Guard®-FM is a 100% solids epoxy mastic used to protect new infrastructure and to rehabilitate existing, damaged, infrastructure.

APPLICATION METHOD
Trowel applied

FEATURES AND BENEFITS
- 100% solids epoxy
- No harmful VOCs
- Convenient and easy to use

RECOMMENDED FOR
- **Manholes, wet wells, vaults and septic tanks**
- **Steel substrates**
- **Floor and wall penetrations/cracks**
- **Simple spot repair**
- **Extreme bonding to nearly all substrates**
- **Fast curing**
- **Easy workability**
- **1/4″ build capability with no sag**
- **No mixing means faster application**

Structure Guard® -RS

Rapid Setting Corrosion Resistant Epoxy

Structure Guard®-RS is a 100% solids, high-build epoxy coating formulated to provide long-term corrosion protection and structural enhancement. Structure Guard-RS sets fast for a quick return-to-service in the most aggressive and turbulent environments.

APPLICATION METHOD
Trowel applied

RECOMMENDED FOR
- **Inverts**
- **Manhole bottoms**
- **Benches**

FEATURES AND BENEFITS
- **100% Solids, No VOCs**
- **Fast set time**
- **Excellent corrosion and abrasion resistance**

Flex Guard®-FM

Flexible Epoxy Mastic

Flex Guard®-FM is a flexible fiber reinforced epoxy mastic for application on metal and concrete substrates, cracks or joints that experience movement. With a 100-150% elongation is it ideal for freeze/thaw and structures that experience temperature fluctuation.

APPLICATION METHOD
For best results, Flex Guard-FM should be applied with a putty knife or trowel, depending on the voids to be filled or covered.

RECOMMENDED FOR
- **Joints**
- **Gaps**
- **Cracks**
- **Holes**

FEATURES AND BENEFITS
- **Fiber reinforced**
- **Flexible, 100-150% elongation**
- **Quick cure time**

Maverick I & I

Polyurethane Grout

Maverick I & I is quick response dual component hydrophobic polyurethane with a 1 - 3 second reaction time. It is designed to stop rapid water flow (up to 50 GPM) leaking from concrete or other underground structures. Since Maverick I & I is hydrophobic, it will not shrink, contains no VOCs and requires no special breathing apparatus or other PPE.

RECOMMENDED FOR
- **Water inflow and infiltration control in manholes, vaults and other concrete, brick or stone structures, above or below grade.**